

The tesa logo is located in the top right corner, featuring the brand name in white lowercase letters on a red background with a blue swoosh.

KNIFELESS OPENING PACKAGING TAPE

tesa® 4190 Knifeless Opening Packaging Tape
Lead to Lots of Advantages and Benefits

- **Safe costs:** eliminates the risk of cutting into your valuable goods and damage of the inner packaging
- **Higher safety:** simple and safe opening without using a knife reduces the risk of human injuries
- **Less claims:** effectively protects the product against tampering
- **Eco-friendly:** full removal of the packaging tape in one swift motion lead to better recyclability

NEW



SIMPLE OPENING. STAY SAFE. SECURED GOODS.



Safe and reliable closed carton due to the strong adhesive of tesa® 4190



Simple and safe opening without using a knife – People stay safe



Protect goods from damage and tempering – Products stay secured

Technical specifications

Product	Total thickness [µm]	Adhesive	Adhesion to steel [N/cm]	Tensile strength [N/cm]	Elongation at break [%]	Additional information
tesa® 4190	45	Synthetic rubber	4.8	43	145	Fingerlift for knifeless opening



tesa® 6075 – Easy application with hand dispenser

The tesa® 6075 hand dispenser takes tesa® packaging tapes up to 75 mm width. Its system of two application rollers offers easy handling and a special blade-protection for safety. The soft gummed handle ensures a secure and comfortable grip.

tesa SE
Phone: +49 40 88899 0
tesa.com/company/locations

tesa.com

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.